

Entranscend Transcend State Subset Subset

SATA III 6Gb/s SSD220S

Transcend's SATA III 6Gb/s SSD220S uses the latest 3D NAND technology that features vertical, stacked expansion of storage cells. By using high-quality flash memory and enhanced firmware algorithms, the SSD220S delivers greater performance and reliability.



3D expansion to break through limits

Unlike planar NAND memory, 3D NAND flash features memory cells stacked vertically in multiple layers. 3D NAND overcomes density limitations of 2D planar NAND, and delivers a higher level of performance and endurance.



Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface and built-in SLC caching technology, Transcend's SSD220S achieves exceptional transfer speeds of up to 550MB/s read and 500MB/s write.



Guaranteed endurance and reliability

Transcend's SSD220S offers great Terabytes Written (TBW) values (up to 320 TB) indicating the total amount of data you can write into the drive over its lifetime. It also features RAID engine and LDPC coding, Garbage Collection, Wear-leveling, and DevSleep.





2.5" Solid State Drive SATA III 6Gb/s SSD220S

Features

- · Up to 550 MB/s read; 500 MB/s write
- · 3D NAND flash memory
- Engineered with a RAID engine and LDPC (Low-Density Parity Check) coding to ensure data integrity; built-in SLC caching technology for exceptional transfer speeds
- Supports DevSleep ultra low power state, S.M.A.R.T., TRIM, and NCQ commands
- Download the SSD Scope software from Transcend's official website



SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

Specification

specification			
Appearance			
Dimensions (Max.)	100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")		
Weight (Max.)	45 g (1.59 oz)		
Storage			
Flash Type	3D NAND flash		
Capacity	120 GB / 240 GB / 480 GB / 960 GB		
Capacity	120 JE / 240 JE / 480 JE / 900 JE		
Operating Environmen	t		
Operating Temperature	0°C (32°F) ~ 60°C (140°F)		
Operating Voltage	5V±10%		
Performance			
Sequential Read/Write	Read: 550 MB/s		
(CrystalDiskMark, max.)	Write: 500 MB/s		
4K Random Read/Write	Read: 65,000 IOPS		
(IOmeter, max.)	Write: 75,000 IOPS		
Mean Time Between Failures (MTBF)	; 1,000,000 hour(s)		
Terabytes Written (Max.)	320 TB		
Drive Writes Per Day (DWPD)	0.3 (3 yrs)		
Note	Speed may vary due to host hardware, software, usage, and storage capacity.		
Warranty			
Certificate	CE/FCC/BSMI		
Warranty	Three-year Limited Warranty		

Ordering Information

120GB	TS120GSSD220S
240GB	TS240GSSD220S
480GB	TS480GSSD220S
960GB	TS960GSSD220S

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



"					
2.5″ SSD	Transcend'	Transcend*	Transcend*		
Comparison	55D2305	55D2205	5503705		
	- Self State Date	Electron trie	Self the Driv		
	SATA III 6Gb/s	SATA III 6Gb/s	SATA III 6Gb/s		
	SSD230S	SSD220S	SSD370S		
Appearance					
Dimensions (Max.)	100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")				
Weight (Max.)	53 g (1.87 oz)	45 g (1.59 oz)	63 g (2.22 oz)		
Storage					
Flash Type	3D NAND flash	3D NAND flash	MLC NAND flash		
Capacity	128GB ~ 2TB	120GB ~ 960GB	32GB ~ 1TB		
Operating Environment					
Operating Temperature	0°C (32°F) ~ 70°C (158°F)	0°C (32°F) ~ 60°C (140°F)	0°C (32°F) ~ 70°C (158°F)		
Performance					
Sequential Read/Write (ATTO, max.)	-	-	560 MB/s 460 MB/s		
Sequential Read/Write	560 MB/s	550 MB/s	520 MB/s		
(CrystalDiskMark, max.)	520 MB/s	500 MB/s	460 MB/s		
4K Random Read/Write (IOmeter, max.)	85,000 IOPS 89,000 IOPS	65,000 IOPS 75,000 IOPS	75,000 IOPS 75,000 IOPS		
Mean Time Between Failures (MTBF)	1,000,000 hour(s)	1,000,000 hour(s)	1,000,000 hour(s)		
Terabytes Written (Max.)	1,120 TB	320 TB	408 TB		
Drive Writes Per Day (DWPD)	0.3 (5 yrs)	0.3 (3 yrs)	0.19 (3 yrs)		
Warranty					
Warranty	Five-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty		
Technology					
Technology TRIM & NCQ Command			,		
S.M.A.R.T.	✓ ✓ ✓	✓ ✓	✓ ✓		
DDR3 DRAM Cache	✓ ✓	-	✓ ✓		
Advanced Garbage Collection	✓ ✓	-	✓		
DevSleep Mode	↓ ↓	 ✓	 ✓		
RAID Engine	↓ ↓	 ✓	-		
LDPC Coding	↓ ✓	 ✓	-		
	• •	•			

*Speed may vary due to host hardware, software, usage, and storage capacity.