



# SATA III 6Gb/s SSD360S

Transcend's SATA III 6Gb/s SSD360S boasts incredibly fast transfer speeds, MLC NAND flash memory, a compact and lightweight design, and shock and vibration resistance. With this solid state drive, you will enjoy a seamless, lag-free computing experience.



## MLC NAND flash inside

Transcend's SSD360S is manufactured with reliable, top-tier MLC NAND flash memory to ensure superior stability and endurance, making it well-suited to high-end applications.



# Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface and a powerful controller, Transcend's SSD360S delivers blazing-fast read and write speeds of up to 560MB/s and 500MB/s.



# Guaranteed endurance and reliability

Transcend's SSD360S offers great
Terabytes Written (TBW) values (up to
230 TB) indicating the total amount of
data you can write into the drive over its
lifetime. It also features Error Correcting
Code (ECC), Garbage Collection,
Wear-leveling, and DevSleep.





#### 2.5" Solid State Drive

# SATA III 6Gb/s SSD360S

### **Features**

- · Up to 560 MB/s read; 500 MB/s write
- · MLC NAND flash memory
- Engineered with ECC (Error Correcting Code) to ensure data integrity
- Supports DevSleep ultra low power state,
   S.M.A.R.T., TRIM, and NCQ commands
- Download the SSD Scope software from Transcend's official website

# Transcend

# SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

# Specification

## **Appearance**

Dimensions (Max.) 100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")

Weight (Max.) 58 g (2.05 oz)

## Storage

Flash Type MLC NAND flash
Capacity 32 GB / 64 GB / 128 GB / 256 GB

## **Operating Environment**

Operating Temperature  $0^{\circ}\text{C}(32^{\circ}\text{F}) \sim 70^{\circ}\text{C}(158^{\circ}\text{F})$ Operating Voltage  $5\text{V}\pm5\%$ 

#### Performance

Sequential Read/Write Read: 560 MB/s (ATTO, max.) Write: 500 MB/s Sequential Read/Write Read: 540 MB/s (CrystalDiskMark, max.) Write: 480 MB/s 4K Random Read/Write Read: 60,000 IOPS (IOmeter, max.) Write: 86,000 IOPS Mean Time Between Failures 1,000,000 hour(s) (MTBF) Terabytes Written (Max.) 230 TB Drive Writes Per Day 0.42 (3 yrs) (DWPD) Speed may vary due to host hardware, software, usage, Note and storage capacity. Warranty

Certificate	CE/FCC/BSMI
Warranty	Three-year Limited Warranty

# **Ordering Information**

32GB	TS32GSSD360S
64GB	TS64GSSD360S
128GB	TS128GSSD360S
256GB	TS256GSSD360S

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



# 2.5" SSD Comparison











SATA III 6Gb/s SSD230S SATA III 6Gb/s SSD220S SATA III 6Gb/s SSD370S SATA III 6Gb/s SSD360S SATA III 6Gb/s SSD340K

Appearance									
Dimensions (Max.)	100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")								
Weight (Max.)	53 g (1.87 oz)	45 g (1.59 oz)	63 g (2.22 oz)	58 g (2.05 oz)	59 g (2.08 oz)				
Storage									
Flash Type	3D NAND flash	3D NAND flash	MLC NAND flash	MLC NAND flash	MLC NAND flash				
Capacity	128GB ~ 2TB	120GB ~ 480GB	32GB ~ 1TB	32GB ~ 256GB	32GB ~ 128GB				
Operating Environment									
Operating Temperature	0°C (32°F) ~	0°C (32°F) ~	0°C (32°F) ~	0°C (32°F) ~	0°C (32°F) ~				
	70°C (158°F)	60°C (140°F)	70°C (158°F)	70°C (158°F)	70°C (158°F)				
Performance									
Sequential Read/Write	-	-	560 MB/s	560 MB/s	550 MB/s				
(ATTO, max.)			460 MB/s	500 MB/s	170 MB/s				
Sequential Read/Write	560 MB/s	530 MB/s	520 MB/s	540 MB/s	510 MB/s				
(CrystalDiskMark, max.)	520 MB/s	480 MB/s	460 MB/s	480 MB/s	170 MB/s				
4K Random Read/Write	85,000 IOPS	50,000 IOPS	75,000 IOPS	60,000 IOPS	70,000 IOPS				
(IOmeter, max.)	89,000 IOPS	75,000 IOPS	75,000 IOPS	86,000 IOPS	40,000 IOPS				
Mean Time Between Failures (MTBF)	1,000,000 hour(s)	1,000,000 hour(s)	1,000,000 hour(s)	1,000,000 hour(s)	1,500,000 hour(s)				
Terabytes Written (Max.)	1120 TB	160 TB	408 TB	230 TB	212 TB				
Drive Writes Per Day (DWPD)	0.3 (5 yrs)	0.3 (3 yrs)	0.19 (3 yrs)	0.42 (3 yrs)	-				

V	V	6	r	r	2	P.	Į	£	v,	
٧	М	a		ш	а			u	y	

Warranty	Five-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty	
Technology						
TRIM & NCQ Command	~	~	~	~	~	
S.M.A.R.T.	<b>✓</b>	~	~	~	~	
DDR3 DRAM Cache	~	-	~	-	~	
Advanced Garbage Collection	~	~	~	~	~	
DevSleep Mode	<b>✓</b>	~	~	~	~	
RAID Engine	~	~	-	-	-	
LDPC Coding	<b>✓</b>	~	-	-	-	

<sup>\*</sup>Speed may vary due to host hardware, software, usage, and storage capacity.